

# GigaSwitch V5 7 Port 54VDC Series

## Contact

Nexans LAN Systems  
Tel.: +49 (0) 2166 27 2220  
sales.ans@nexans.com

## LANactive 7 Port Managed Full Gigabit Ethernet FTTO Switch

- 3 Uplink Ports (2x SFP and 1x RJ45)
- Power over Ethernet (PoE+), up to 150W
- Efficient Energy Management
- Memory Card Slot
- Input voltage range 46 ... 57V DC

## Description

Nexans LANactive GigaSwitch V5 series is designed for the installation in Fibre to the Office (FTTO) networks. The latest generation of FTTO switches is equipped with a state-of-the-art network processor and provides enhanced performance, security and redundancy functionality.

### 7 Port Version

The GigaSwitch version with seven ports is part of the latest V5 series. This special variant with three uplink ports allows a redundant connection of the GigaSwitch via fibre optic. The RJ45 uplink can be used for connecting an additional Wireless LAN Access Point. All uplinks support Link Aggregation for providing redundancy and double bandwidth up to 2Gbps.

### Snap-In Installation

The very compact design of the GigaSwitch allows a tool-less snap-in installation into the standard 45 mm cable duct systems or floor boxes without special mounting accessories.

### Power over Ethernet

Up to 5x connected Ethernet devices can be supplied with Power over Ethernet. According to the latest IEEE 802.3at (PoE+) standard, up to 30 watts per port are available for each connected device, with total budget of 150 watts.

### Memory Card

The optional memory card automatically saves the complete current configuration and firmware of the device. In case of failure, this feature allows an easy exchange of the hardware without additional configuration. In addition, each memory card can be delivered with its own MAC address that is adopted by the switch.

### Switch Management and Zero-Touch Configuration

Nexans Device Manager NEXMAN allows a simple and secure configuration of all device parameter of the GigaSwitch series. With NEXMAN a larger number of GigaSwitches can be managed and monitored at the same time. In combination with Nexans Zero-Touch Configuration, NEXMAN allows automatic distribution of configurations and firmware updates. A pre-configuration of the switches is not necessary.



Made in Germany

**LANactive**  
Switch to the future

**NEXMAN**  
ClientController



## Standards

IEEE 802.3  
IEEE 802.3u  
IEEE 802.3ab  
IEEE 802.3af  
IEEE 802.3at  
IEEE 802.3z  
IEEE 802.3x  
IEEE 802.1AB  
IEEE 802.1D  
IEEE 802.1Q  
IEEE 802.1X  
IEEE 802.1AX  
IEEE 802.3ad



Real-Time OS  
Yes



PoE/PoE+  
Yes



Compact design  
45x90mm



Noiseless  
Yes



Fast Installation  
Yes



Redundancy  
Yes



Operating Temperature  
0 ... 45 °C



Electromagnetic Shielding  
Yes

**Nexans**

# GigaSwitch V5 7 Port 54VDC Series

## Contact

Nexans LAN Systems  
Tel.: +49 (0) 2166 27 2220  
sales.ans@nexans.com

## Hardware Features

Ordering Information	GigaSwitch V5 TP(PSE+) SFP-2VI 54VDC	GigaSwitch V5 TP SFP-2VI 54VDC
Article Number	88303910	88303920
<b>Interfaces</b>		
User Ports (RJ45)	4x 1000Base-T	
Uplink Ports (SFP)	2x 100/1000Mbps	
Uplink Ports (RJ45)	1x 1000Base-T	
RJ45 Ports	Auto-Negotiation, MDI/MDI-X Auto-Cross Over and Auto-Polarity	
Eco Mode for RJ45 Ports	Yes	
Rotatable Head Module	Yes	
<b>Power over Ethernet</b>		
Number of PoE User Ports	4x PSE(PoE+) acc. to IEEE802.3at	
Number of PoE Uplink Ports	1x PSE(PoE+) acc. to IEEE802.3at	-
PoE Mode	30W per Port, Mode A, Pin 1-2/3-6	
Max. PoE power budget	150W	120W
<b>Diagnostic Functions (Interfaces)</b>		
Digital Diagnostics Monitoring Interface	Yes	
Twisted Pair Cable Diagnostic	Yes	
<b>General</b>		
Dimensions [W x H x D]	96mm x 45mm x 69mm	
Installation Depth	35mm	
Material	zinc diecasting / stainless steel	
Colour	Pure White, like RAL 9010	
Ambient Temperature	Operation: 0 ... 45°C, Storage: -20 ... 85°C	
Relative Humidity	20 ... 90% (non-condensing)	
Weight	290g	
MTBF	> 750,000h	
<b>Power Supply</b>		
Input Voltage	46 ... 57V DC (typ. 54V DC)	
Power Consumption	4.9W (standby) ... 5.3W (typ.) ... 6.5W (fully connected)	
Heat Output	23Btu(IT)/h	
Connector	3-pin connector with plug-in screw terminal (up to 2.5mm <sup>2</sup> ) / (+) (-) (FPE)	
<b>CE - Conformity</b>		
Electro Magnetic Capability Directive	2014/30/EU	
Low Voltage Directive	-	
RoHS 2	2011/65/EU	
Engineering Standards	EN 62368-1, EN 55032, EN 55024, EN 50581	

# GigaSwitch V5 7 Port 54VDC Series

## Contact

Nexans LAN Systems  
Tel.: +49 (0) 2166 27 2220  
sales.ans@nexans.com

## Switch and Software Features

### Switching Parameters

Switching Type	Store-and-Forward, self-learning
Switching Capacity, non-blocking	20Gbps
Packet Forwarding Rate per Port	2x 1.488Mpps
Max. Frame Size	9.600Bytes (Support of Jumbo frames)
Packet Buffer	512kBytes
Latency (RFC1242)	100Mbps / 64Byte (FIFO/LIFO) 9µs / 9.3µs 100Mbps / 1518Byte (FIFO/LIFO) 125µs / 4µs 1000Mbps / 64Byte (FIFO/LIFO) 2.7µs / 2.2µs 1000Mbps / 1518Byte (FIFO/LIFO) 15µs / 2.5µs
MAC-Address Table	8.192 MAC-Addresses
VLANs	IEEE802.1q with up to 256 Groups
Quality of Service Layer 2	IEEE802.1p Class of Service (4 Queues per Port)
Quality of Service Layer 3	RFC2474/3168 DSCP (4 Queues per Port)
Bandwidth Limitation	Bitrate
Energy Efficient Ethernet	IEEE802.3az
Flow Control	IEEE802.3x
Fabric Attach	Basic Fabric Attach Client Support

### Management

LEDs	On-Board High-Performance Management
Zero-Touch Configuration	Management, Port Status and Activity, Memory Card
IP-Address	Via NEXMAN Controller
DHCP-Client	IPv4, IPv6
DHCP Relay Agent	DHCP, DHCPv6
File Transfer	Yes
Console Port	TFTP, SCP
Web-Interface	V.24 with Nexans Console Cable
Command Line Interface	HTTP, HTTPS
Scripting	SSH, Telnet, V.24
SNMP	Yes
Syslog	SNMPv1, v2c, v3
Discovery Protocols	Yes
Time Synchronisation	LLDP (IEEE802.1AB), LLDP-MED (ANSI/TIA-1057), CDP
Port Statistics	SNTP

### Redundancy

Redundancy Protocols	STP, RSTP, MSTP, MRP
Link Aggregation	LACP

### Security

Password Protection	Two Access Levels (R/W or R/O)
Authentication via Radius and TACACS+	CLI and NEXMAN
Access Control List (ACL)	Layer 2 and Layer 3
ACL for Management Interface	Up to 16 Access Control Lists
Portsecurity via MAC-Address	Up to 3 predefined MAC-Addresses
Portsecurity via Radius	IEEE802.1x with MAC Bypass
DHCP Snooping	Yes
Loop and Broadcast Limiter	Yes
Firmware Update	Dual Firmware Image
Configuration-/Reset Button	Yes / Yes
Memory Card	Micro SD-Card, optionally with fixed MAC-Address



# GigaSwitch V5 7 Port 54VDC Series

Contact  
Nexans LAN Systems  
Tel.: +49 (0) 2166 27 2220  
sales.ans@nexans.com

## Dimensions

